

SEAHORSE 3 ROV SYSTEM

Seahorse 3 remotely operated vehicle is a 125 HP Work Class ROV, high performance professional ROV system with Top-hat TMS which can be used for a variety of underwater tasks such as drilling support, observation, survey and NDT inspections, construction, intervention, IRM, etc. The stainless steel open-frame design, the abundance of space and the generous payload capability provide a versatile solution for the fitting of additional equipment and sensors.



Seahorse 3 Work Class ROV System

125 HP of Hydraulic Power

- 125 HP
- Auto heading, depth, altitude, auto park
- Serial, Video, Ethernet via single mode fibre
- HD camera capability (IP)
- PC Based control system
- Survey sensor integrated capacity



GENERAL SPECIFICATIONS

Depth rating:	1000 msw
Dimensions (L x W x H):	2.5 x 1.5 x 1.9 m
Weight in air:	2.8 ton
Through- frame lift:	1.0 ton
Payload:	250 kg

PERFORMANCE

Power:	125 HP
Thrusters (Horizontal):	4 x SA300
Thrusters (Vertical):	3 x SA300
Forward, aft, lateral BP:	650 kg
Vertical up pull:	500 kg
Forward, aft speed:	3.0 knots
Lateral, Vertical speed:	2.5 Knots

AUTO FUNCTIONS:

Auto heading:	± 2.5 degrees
Auto depth:	± 15 cm
Auto altitude:	± 15 cm

SENSORS

Gyro (MRU):	Tritech iGC
Navigation compass:	Tritech
Depth Sensor:	Digiquarts
DVL:	Optional
Altimeter:	Kongsberg 807
Sonar:	Kongsberg MS 1000

CAMERAS & LIGHTS

First Pan & Tilt:	1 x Tritech Hydraulic
Second Pan & Tilt:	Optional
Low light B/W:	1
Colour CCD Zoom:	1
Colour CCD Fixed focus:	2
Dimmable lights:	4
Flood lights:	2

MANIPULATORS

7 Function:	Schilling T3
5 Function:	Schilling Rig Master

TOP HAT MANAGEMENT SYSTEM

Dimensions (D X H):	2 x 2.2 m
Weight in air:	3 ton
Max tether length:	250 m
Depth sensor:	Transponder
Colour camera:	2
Lights:	2

CONTROL, WORKSHOP CONTAINERS

Control	20 feet ISO
Work Shop	14 feet ISO

LAUNCH & RECOVERY SYSTEM

Type:	A-Frame
Dimensions (L x W x H):	6.0 x 2.99 x 3.5 m
Max height:	9.0 m
A-Frame weight:	12 ton
Winch (L x W x H):	2.9 x 2.99 x 3.0
Winch weight:	16 ton
Winch max umbilical:	1,500 m
HPU (L x W x H):	2.8 x 1.5 x 1.7
HPU Weight:	3,500 kg

STANDARD OPERATIONAL LIMITS:

Beaufort:	6
-----------	---

ELECTRICAL REQUIRMENTS:

ROV, Control van:	380/480 VAC, 50/60 Hz 3PH, 250A
LARS:	400/460 VAC, 50/60 Hz 3PH, 200A

ROAD TRANSPORTATION:

Numbers of trucks:	3-4
--------------------	-----